

# EP-TRACER<sup>®</sup> 2 Stationary

The electrophysiological measurement system with a fully-integrated stimulator

**schwarzer  
cardiotek**  
SMART. PRECISE. RELIABLE.



The EP-TRACER 2\* with fully-integrated stimulator can be used for both clinical and experimental EP studies.

The EP-TRACER 2 Stationary version is provided with two high resolution monitors; one that displays real-time signals while the second can be used for playback and analysis. The EP-TRACER 2 is installed below or

near the patient table and is connected via a fiber optic cable to the control table PC.



\* EP-TRACER with new software version 2.2

## Features of the EP-TRACER 2 Stationary

### Amplifier

EP-TRACER 2 amplifiers offer the connection of either 20, 52 or 84 intracardiac channels. All amplifier models allow connection of 12 surface ECG channels and 6 auxiliary channels which, for example, can be used for the measurement of invasive blood pressure.

### Integrated stimulator

The EP-TRACER 2 is equipped with a built-in 2-channel stimulator. The software allows stimulation on any intracardiac channel with the click of the mouse, without further external wiring or equipment. Stimulation protocols are easily customized and accessed, thus further streamlining the procedural workflow.

### Software

The EP-TRACER 2 software provides an intuitive interface that supports your requirements at every stage of the procedure. Special

display modes, such as triggered mode, pressure mode and multiple user-configurable split-screen modes provide the perfect framework to display data from multiple sources. For example, surface and intracardiac ECG signals, invasive blood pressure, as well ablation data (RF- and cryo-ablators supported) can all be displayed within your customized layout.

One-touch commands to start/stop stimulation, decrement interval time, load a saved stimulation protocol, save events, add comments etc., allows for the seamless operation of the EP-TRACER within your preferred workflow. All events are time-stamped and added to the user-customizable procedure log to facilitate reporting and later review from anywhere in the hospital network using our specialized review software.



### New in software version 2.2: Expanded functionality with improved usability

- One-click report generation. Customizable templates allow full flexibility. Patient data, procedure log, including key ablation data (e.g. for RF: duration, temperature, power, impedance), comments, screenshots etc. all automatically entered into your template with a single click.
- Improved icon-based operation: Pin-drop, Screenshot and AutoText features for rapid procedural annotation and streamlined reporting.
- Improved layout for display of intracardiac pressure waveforms during EP studies.

# EP-TRACER® 2 Stationary

The electrophysiological measurement system with a fully-integrated stimulator



## Components

- EP-TRACER 2 Stationary
  - Isolation transformer, ca. 500VA\*
  - PC system \* (Windows 7, 32bit)
  - 2 × 21" monitors \*
  - Laser printer \*
- Software EP-TRACER 2
  - Recording software
  - Instruction manual (on a CD)
  - Review software
  - Dongle licence key
- EP-amplifier
  - 20, 52 or 84 intracardiac channels
  - 12 surface ECG channels
  - 6 auxiliary channels; e.g. for the invasive measurement of blood pressure
  - Integrated stimulator with 2 outputs
  - Allows custom stimulation via intracardiac channels without external wiring
  - Input mode: bipolar or unipolar
  - Isolated power supply
- Catheter connection boxes
- Power-box, 100-240 V
- Filter set with EP-TRACER 2 70 and 102
- Cabling
  - Cable for catheter connection box (around 3 m)
  - ECG cable with electrodes
  - Carbon-fiber cable RTBG-3605, L = 90 cm

\*Not part of the certified medical product

## Technical details

<b>Medical device directive (93/42/EEC):</b>	Class IIb
<b>EP-TRACER 2</b>	
<b>Intracardiac channels</b>	20/52/84
Sampling rate	1 kHz per channel
Amplification factor	0.1 - 25
Catheter connection box	2/4/6 × DIN DB25 Input modes: bipolar and unipolar
<b>ECG-Channels</b>	Electrode connections: R, L, F, N, C1-C6 Standard: DIN DB15 Leads I, II, III, aVL, aVR, aVF C1-C6 Calibration equivalent to 1 mV
<b>Additional channels</b>	6 AUX channels Connections: 3 × 9 pin REDEL (2 channels per connection) Input mode: bipolar
<b>Current leakage</b>	< 50 µA
<b>Back-up stimulation mode</b>	60 beats per min at Out1-Out2 simultaneously; current = 8mA, pulse amplitude = 2msec
<b>Stimulator</b>	Current 0 - 25.5mA (customizable) Minimum increment 0.1 mA Maximum output-voltage: 20 V Safety stimulation: 60 beats/min Connections: 4 × 2mm banana plug
<b>Analog/digital converter</b>	Resolution: 12 bit (20 bit dynamic) Bit weight: 1.25 µV/ LSB
<b>Computer operating system</b>	Windows 7, 32bit
<b>Monitors</b>	2 × 21" high resolution
<b>Printer</b>	Laser
<b>Applicable standards</b>	IEC 60601-1:2005 + A1:2012 / IEC 60601-1-2: 2007 IEC 60601-1-6: 2010 + A1:2013 / IEC 60601-2-27: 2011 IEC 60601-2-34: 2011 / IEC 62366: 2007 + A1:2014 IEC 62304: 2006
<b>Patient safety</b>	Safety class I, type CF according to IEC 60601-1; Patient connections protected against the effects of defibrillation impulses
<b>Dimensions (h × w × t)</b>	
EP-TRACER 2 38/70/102	60 × 280 × 270 mm / 110 × 290 × 260 mm / 110 × 290 × 260 mm
<b>Weight</b>	
EP-TRACER 2 38/70/102	ca. 2.2 kg / 3.3 kg / 3.8 kg
Monitors	ca. 10.6 kg
<b>Labelling</b>	only for EP-TRACER 2 medical device
	CE 0197

Notice: Content may be subject to change